


Connection Value Gear

Studio Star drive	
EL-Tubular drive / S-ABS-Tubular drive	50/08, 12, 20, 30, 40
Turning moment	8, 12, 20, 30, 40 Nm
Rotation speed	12 min ⁻¹
Type of current	1 phase alternating current
Voltage	220V / 50Hz
Current consumption	0,80 A
Capacity	184 W
Duty rating	Ca. 5 min.
Accuracy of end position	Class 2; ± 5 %
Warning! A parallel connection of S-ABS-Tubular drive is not possible.	

Wiga Star drive	
ABS Tubular Drive	60/55
Turning moment	55 Nm
Rotation speed	13 min ⁻¹
Type of current	1 phase alternating current
Voltage	220V / 50Hz
Current consumption	1,10 A
Capacity	253 W
Duty rating	Ca. 5 min.
Accuracy of end position - optional	Class 2; ± 5 %
Warning! A parallel connection of the gear is not possible.	

	<p>The electrical connection of the roller shutter and the control unit must only be completed by skilled electricians in compliance with the enclosed connecting diagram and the national and international legal regulations, e.g. DIN EN 60335-1 (VDE 0700-1), DIN EN 60335-2-97, DIN EN 60204-1 (VDE 0113-1) etc. Furthermore the regulations of the local electric utility, the Employer's Liability Insurance Association and the Accident Prevention Regulation have to be strictly followed.</p> <p>The roller shutter and the control unit can only be connected to an in-house network which is equipped with a ground fault circuit interrupter.</p>
---	---